PS-32 Gasoline chain saw

Entry model. Easy operation, fitted with professional features. Very easy starting.





Easy Start: Spring assisted starter combined with optimized engine management



Touch&Stop one lever operating





Fuel pump (Primer)



Metal spike bar

Techni	cal speci	fications

Displacement	32 cc (1.95 cu. in)
Power rating	1.35 kW (1.8 HP)
Max engine speed	12,800 rpm
Net weight	4.1 kg (9.02 lbs)
Fuel tank capacity	0.4 l (13.5 oz)
Oil tank capacity	0.28 (9.5 oz)
Vibration damping	yes

- Easy Start: Spring assisted starter combined with optimized engine management signitificantly reduces resistance
- Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.
- Primer pump: Engine starts instantly after refuelling
- . MPI technology (Memory-Power-Ignition) for easy restart
- Metal spike bar as standard
- SafetyMatic chain brake.
- Professsional quality centrifugal clutch
- Outside sprocket

Chain tensioning	Lateral tensioning
Automatic oilpump	yes
Catalytic converter	yes
Standard guide bar	14"
Optional guide bars	16"
Chain pitch	3/8 "
Chain gauge	.050 "

- Adjustable metal chain oil pump
- Catalytic converter to clean the exhaust gases
- Big tank cap, easy reachable. S-form with acme thread for easy operation
- 33 cm markings on the rear handle for cutting wood to length
- 4 steel springs for low vibration
- Lateral chain tensioning
- Two bar studs for reliable bar fastening

DOLMAR Power Products . PO Box 5007 . Alpharetta, GA 30023-5007



www.dolmarpowerproducts.com